

PRODUCT DESCRIPTION

BF PRINTTOPG (glossy) and BF PRINTTOPM (matte) are two thin polyurethane white films printable with solvent, eco-solvent and latex inks and are suitable for heat transfer on cotton fabrics, polyester, nylon Lycra and acrylic garments.

Available two BF PRINTTOP version:

- BF PRINTTOPM-G/P WITH PAPER BACKING: not adhesive, really easy to transfer;
- BF PRINTTOPM-G WITH PET BACKING: adhesive, stability during printing.

We recommend the BF MYLAR film as a transfer tape and as a protection during the heat transfer, and then remove it while hot.

APPLICATION STEPS

- Print - do not mirror
- Cut - 45° blade
- Weed excess material
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 145°C/295°F
- Place your graphic on the shirt
- Press it - 145°C/295°F for 8 seconds
- Remove BF MYLAR - hot

SIZES

H 50 cm L 25 mt / 12,5 mt / 5 mt

H 75 cm L 25 mt (upon request)

H 100 cm L 25 mt (upon request)

H 150 cm L 25 mt (upon request)

Oeko-Tex
Standard 100
Class I



Comply with
regulation REACH
n°1907/2006/EU

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03

TECHNICAL DATA



Film: PU/polyurethane



Thickness: 60μ (±5%)



Liner: adhesive PET
available also in paper (P)



Finish: BF PRINTTOPM matte
BF PRINTTOPG glossy



Inks: solvent, eco-solvent, latex

PLOTTER SETTING



Cut settings: do not mirror



Blade: 45°



Minimum cut: 1 cm

APPLICATION



Temperature: 145°C - 295°F



Time: 8''



RLiner removal: hot



Pressure: medium - 3,5 bar - 50 PSI



Textile: organic, synthetic, mixed, nylon,
stretch and treated fabrics

WASH RESISTANCE

First wash after application

12 hours

Max temperature*

40°C - 104°F

Dry clean



Dryer



*Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

BF PRINTTOPM-G
PRINT&CUT

- *Soft touch*
- *Stronger adhesive to perform on treated or coated fabrics*
- *Available also with liner in paper*