

PRODUCT DESCRIPTION

BF PRINTSU is a polyurethane sublistop and block-out film printable with all solvent, eco-solvent and latex based inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments.

BF PRINTSU is specially formulated to prevent the pigment migration from sublimation dyed textiles and keep any graphic looking bright on any kind of polyester garment! Thanks to its sticky carrier small letters and drawings can be easily cut by all current cutting plotters after the printing process.

We recommend using BF MYLAR as a transfer tape and as a protection during the heat transfer.

APPLICATION STEPS

- Print - do not mirror
- Cut - 45° blade
- Weed excess material
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 140°C/285°F
- Place your graphic on the shirt
- Press it - 140°C/285°F for 10 seconds
- Remove BF MYLAR - hot

SIZES

H 50 cm L 25 mt / 12,5 mt / 5 mt

H 75 cm L 25 mt (upon request)

H 100 cm L 25 mt (upon request)

H 150 cm L 25 mt (upon request)

Oeko-Tex
Standard 100
Class I



Comply with
regulation REACH
n°1907/2006/EU

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03

TECHNICAL DATA



Film: PU/polyurethane



Thickness: 120μ (±5%)



Liner: adhesive PET



Finish: opaque



Inks: solvent, eco-solvent, latex

PLOTTER SETTING



Cut settings: do not mirror



Blade: 45°



Minimum cut: 2 cm

APPLICATION



Temperature: 140°C - 285°F



Time: 10''



Liner removal: hot



Pressure: medium - 3,5 bar - 50 PSI



Textile: synthetic, sublimated fabrics

WASH RESISTANCE

First wash after application

wait 12 hours

Max wash temperature*

40°C - 104°F

Dry clean



Dryer



*Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

BF PRINTSU
PRINT&CUT



- Prevents the color's pigments migration from the fabric to the film's surface
- Blockout
- Washing resistant and durable